


LE910C4-NF Series

LTE Cat.4 150/50 Embedded



Product Description

The LE910C4-NF series of 4G LTE modules are compliant with the 3GPP Release 10 and are available with optional quad-constellation GNSS capability. This compact LGA form factor family is available in a variety of configurations, supporting both multi-mode and fallback as needed for specific regions, carriers, and use cases. The LE910C4-NF is supporting the latest required band 14 for dedicated public safety, first responder networks carrier implementation.

Key Benefits

- Best-in class 3GPP rel. 10 platform
- Easy to integrate with peripherals and actuators using USB 2.0 HS, UART and user definable GPIOs
- Internet friendly with integrated TCP/IP and UDP/IP stacks
- Simple drop-in migration and technology design reuse path to 2G and 3G with any xE910 module
- Over-the-Air firmware update
- Embedded GNSS solution

Family Concept

The LE910C4-NF is a member of Telit's flagship xE910 module family delivering 4G radio access technology in the 28.2 x 28.2 x 2.2 mm family form factor. The Telit xE910 Unified Form Factor Family is comprised of 2G, 3G, and 4G, 3GPP and 3GPP2 products sharing a common form factor as well as electrical and programming interfaces which allows developers to implement a "design once, use anywhere" strategy.

Variants

4G North American market for AT&T, Verizon and T-Mobile

AVAILABLE FOR

[North America](#)

IoT Connectivity and Portal Ready

This product is capable of supporting the extensive suite of Value Added Services from IoT Connectivity including Module Management and others which make the management of IoT deployments under mobile networks effective, enhancing profitability and reliability. It is also Portal-ready which means that the AT command library in this module includes a set of high-level commands designed exclusively for quick and hassle-free on-boarding of the device to the portal and to back-end systems and servers. Telit Portal-ready modules powered by deviceWISE make application-level data flows and controls simple to program, maintain and improve.

Combine your Cellular module with

Short Range modules



www.telit.com

Complete, Ready to Use Access to the Internet of Things



LE910C4-NF

Market	North America (Dedicated public safety, first responder networks, AT&T, VZW, T-Mobile)
Frequencies	
4G	B12, B14, B4, B2, B5, B13, B71
3G	B2, B5

LE910C4-NF Series

Product Features

- LTE FDD Cat.4, 3GPP release 10 compliant
- Rx Diversity and MIMO DL 2x2
- Single Rx option
- VoLTE support
- SMS over IMS
- Built in UDP/TCP/FTP/SMTP stack • I
- Pv4/IPv6 stack
- Control via AT commands according to 3GPP
- TS 27.005, 27.007 and Telit Custom AT commands
- SIM application Tool Kit 3GPP TS 51.014
- OMA-DM Telit Software Management
- Simultaneous support of GPS, Glonass, Beidou,
- Galileo, QZSS

Data

LTE Cat. 4

- Uplink up to 50Mbps
- Downlink up to 150 Mbps

DC-HSPA+ 42 Mbps

Environmental

- Dimensions 28.2 x 28.2 x 2.2mm
- Temperature Range
-40°C to +85°C
- REACH and RoHS compliant

Interfaces

- 181-pin LGA interface
- 10 I/O ports (@1.8V) including multifunctional I/Os
- USB 2.0 HS / HSIC
- UART
- SPI
- PCM
- 1.8 V / 3 V SIM interface
- RF pad, RX Div. & MIMO pad

Approvals

- FCC/IC, PTCRB, GCF

Electrical & Sensitivity

- Output power
 - Class 3 (0.2 W, 23 dBm) @ LTE
- Supply voltage range:
 - Nominal: 3.8 VDC
 - Range: 3.3 - 4.2 VDC

Request a **FREE** project review >

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

www.telit.com/facebook | www.telit.com/googleplus | www.telit.com/linkedin | www.telit.com/twitter